



# Pilot Ladder














Pilot ladder secured using ship made brackets. The weight of the pilot will be supported by one step only. The hard edge of the top hull plate may damage the ropes.






Pilot ladder should not be secured by shackles or tying to ship side rails. These rails are easily damaged and their strength cannot be guaranteed.











If the distance from waterline to the boarding point is more than 9 metres then a combination arrangement must be used - the accommodation ladder combined with a proper pilot ladder. Check the rules for rigging distances.

### Global service built around you





## Checklist

#### PILOT LADDER

Use with onboard procedures, SOLAS Chapter V, and IMO approved pilot boarding card.

#### Rigging

_

#### Disclaimer

This information is intended purely as guidance and is to be used at the user's own risk. No warranty of accuracy is given and users of the information are expected to satisfy themselves that the information is relevant and suitable for the purposes to which it is applied. No responsibility is accepted by the North of England P&I Association Limited, or by any person, firm, corporation or organisation who or which has been in any way concerned with the furnishing of data, the development, compilation, or publication, for the accuracy of any information or advice given herein or for any omission here from or for any consequences whatsoever resulting directly or indirectly from compliance with or adoption of guidance contained therein. No part of this publication may be reproduced, stored in a retrieval system or transmitted in any form or by any means (electronic, mechanical, photocopying, recording or otherwise) without the written permission of the publisher.



